2015 JINST 10 C04038

RECEIVED: November 5, 2014 ACCEPTED: December 29, 2014 PUBLISHED: April 30, 2015

16th International Workshop on Radiation Imaging Detectors 22–26 June 2014, Trieste, Italy

Diamond particle detectors systems in high energy physics

A. Oh for the RD42 collaboration

School of Physics and Astronomy, University of Manchester, Manchester, U.K.

E-mail: alexander.oh@manchester.ac.uk

ABSTRACT: With the first three years of the LHC running complete, ATLAS and CMS are planning to upgrade their innermost tracking layers with more radiation hard technologies. Chemical Vapor Deposition (CVD) diamond is one such technology. CVD diamond has been used extensively in beam condition monitors as the innermost detectors in the highest radiation areas of BaBar, Belle, CDF and all LHC experiments. The lessons learned in constructing the ATLAS Beam Conditions Monitor (BCM), Diamond Beam Monitor (DBM) and the CMS Pixel Luminosity Telescope (PLT) all of which are based on CVD diamond with the goal of elucidating the issues that should be addressed for future diamond based detector systems. The first beam test results of prototype diamond devices with 3D detector geometry should further enhance the radiation tolerance of this material.

KEYWORDS: Diamond Detectors; Radiation-hard detectors